# **Cat<sup>®</sup> Pneumatic Tools**



## The power to get the job done

Cat<sup>®</sup> pneumatic tools provide power to finish the job quickly and easily. There are many pneumatic tool models from which to choose, each with the following features and benefits:

- Lightweight for ease of handling
- Aluminum housing for durability and long life
- Powerful motor
- European Union compliant (CE marked)



### **Cat Pneumatic Tools**

#### **Sanders and Polishers**

Part No.	Size/Type
222-3084	5-in Compact Sander
222-3063	6-in Orbit Palm Sander
222-3068	6-in Dual Action Sander
222-3064	7-in Heavy Duty Angle Sander
222-3067	Heavy Duty In-line Sander
222-3065	7-in Vertical Polisher
222-3069	7-in Heavy Duty Angle Polisher

- Ball bearing-mounted air motor reduces vibration and operator fatigue
- Ball bearings prolong motor life
- Durable aluminum housing reduces weight and provides long life
- Full choice of RPM ranges
- Compact design for easy maneuvering in restricted areas

Recommended air pressure for 222-3068 dual action sander is 410 kPa (60 psig). Recommended hose size for 222-3065 is 10 mm (<sup>3</sup>/<sub>8</sub> in). Recommended hose size for other sanders and polishers is 8 mm (<sup>5</sup>/<sub>16</sub> in).

For a listing of Cat abrasive discs, please refer to PECJ0003, Shop Supplies and Hand Tools Catalog.

#### **Air Grinders**

Part No.	Туре
222-3071	Angle Die Grinder
222-3072	Vertical Die Grinder
222-3074	Medium Mini Die Grinder
222-3076	Right Angle Die Grinder
222-3077	Extended Die Grinder

- Ball bearing-mounted air motor reduces vibration and operator fatigue
- Ball bearings prolong motor life
- Powerful .2 horsepower motor
- Paddle-style variable-speed safety trigger prevents accidental startups
- Durable aluminum housing reduces weight and provides long life
- Compact design for easy maneuvering in restricted areas
- Angled-head grease fitting allows lubrication of gear train

Recommended hose size for 222-3071 and 222-3072 air grinders is 10 mm ( $\frac{3}{6}$  in). Recommended hose size for 222-3074, 222-3076 and 222-3077 grinders is 8 mm ( $\frac{5}{6}$  in). Air inlet thread size for 222-3072 is  $\frac{1}{2}$  in – 18 NPT.

For a listing of Cat grinding wheels, please refer to PECJ0003, Shop Supplies and Hand Tools Catalog.



## **Air Drills**

Part No.	Size/Type
222-3061	⅔-in Reversible
222-3062	<sup>1</sup> / <sub>2</sub> -in Reversible

Chucks for 222-3061 Air Drill		
234-0544	Keyless ¾-in Chuck	
243-6496	Keyed ¾-in Chuck	

#### Chucks for 222-3062 Air Drill

234-0545	Keyless ½-in Chuck
243-6495	Keyed ½-in Chuck

#### Air Hammer

Part No.	Туре	
222-3080	Long Air Hammer	

Part No.	Description	Size	Length
223-4352	Sheet Metal Ripper	% in	5 in
223-4353	Flat Chisel	3⁄4 in	7 in
223-4354	Panel Cutter	3⁄4 in	6 in
223-4355	Slitting Chisel	1 in	6% in
223-4356	Weld Breaker	% in	6¾ in
226-0102	Punch, 15 Degree	0.4 in	9 in
226-0124	Straight Punch	0.4	9 in

#### Air Ratchet

Part No.	Size
222-3059	³∕₀ in



Recommended hose size for 222-3059 air ratchet is 10 mm (% in).

- Ball bearing-mounted air motor reduces vibration and operator fatigue
- Ball bearings prolong motor life
- Powerful, reversible .3 horsepower motor
- Contoured, button-style variable-speed trigger is versatile and easy to use
- Durable aluminum housing reduces weight and provides long life
- Compact design for easy maneuvering in restricted areas

Recommended hose size for air drill is 8 mm (5/16 in).

For a listing of Cat drill bits, please refer to PECJ0003, Shop Supplies and Hand Tools Catalog.

- Durable aluminum housing reduces weight and provides long life
- Variable-speed trigger is easy to use and versatile
- Long barrel for easier access to hard-to-reach areas
- Slices bushings, cylinder sleeves. Cuts exhaust and tail pipes
- Air-directed exhaust
- Nylon friction plugs
- Air line filter
- QC chuck

Recommended hose size for air hammer is 10 mm (¾ in).

- Ball bearing-mounted air motor reduces vibration and operator fatigue
- Ball bearings prolong motor life
- Fast and powerful—200 RPM free speed, 250 in-lb torque output
- Paddle-style variable-speed trigger is versatile and easy to use
- Durable aluminum housing reduces weight and provides long life

## **Cat Pneumatic Tools**

#### Shears



- Pistol grip for comfort
- Handle exhaust directed away from operator
- Ball bearing-mounted rotary air motor for long service

Recommended hose size for 222-3083 shears is 8 mm (5/16 in).

#### **Air Engraver**



- Knurled fingertip control
- Rugged metal housing
- Includes coarse needle
- Additional tips available

Recommended hose size for air engraver is 10 mm (3% in).

Except where noted, all tools have a recommended air pressure of 620 kPa (90 psig) and an air inlet thread size of  $\frac{1}{4}$  in – 18 NPT.

Information on impact wrenches can be found in PECJ0003, Shop Supplies and Tools Catalog.

For more information, see us today or visit our Web site at www.cat.com

#### CAT<sup>®</sup> DEALERS DEFINE WORLD-CLASS PRODUCT SUPPORT.

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts keeps your entire fleet up and running to maximize your equipment investment.



PEHJ0087-02 www.cat.com

