

Cat[®] TDTO[™]

Transmission and drive train oil for Cat transmissions, final drives and wet brake compartments.

SAE 10W, SAE 30, SAE 50



Recommended Use

- Preferred lubricant for Cat power shift transmissions, and most final drives and wet brake compartments
- Cat machine compartments where TO-4 and TO-4M specification oils are recommended
- Other manufacturers' machines that recommend TO-4 or TO-4M or specification oils for their transmissions, final drives and wet brake compartments (See "Typical Characteristics" on page 2 for more information)

Discover the Difference

Cat TDTO is developed, tested and approved by Caterpillar to meet the same high standards as Genuine Cat Parts.

- Factory-Fill—Used as standard factory-fill for Cat machine compartments where TO-4 oils are specified.
- Longer Clutch Life—Prolongs clutch disc life up to 45%.
- Optimum Wear Life—Ensures long life and excellent performance for gears, bearings and friction disc material.
- System-Matched Formula—Engineered as an integral part of Cat power shift transmissions, most wet brake compartments, and hydrostatic systems



Tested Beyond Industry Standards

The TO-4 specification defines a minimum standard of performance for transmissions and drive train oils, but Cat TDTO is required to pass five additional Caterpillar tests. It is only through these tests and thousands of hours of field experience that Caterpillar is confident in saying Cat TDTO will deliver long life and excellent performance when used in Cat transmissions and final drives.

Typical Characteristics*

SAE Viscosity Grade	10W	30	50
Caterpillar Test	TO-4	TO-4	TO-4
Allison Test	C-4	C-4	C-4
ISO Viscosity Grade	42	100	—
Gravity, API (ASTM D287)	27.9	27.0	24.7
Flash Point, °C (°F) (ASTM D92)	202 (395)	224 (435)	240 (464)
Pour Point, °C (°F) (ASTM D97)	-33 (-27)	-18 (0)	-15 (5)
Viscosity			
CCScP @ -25° C (ASTM D5293)	6840	—	—
CCScSt @ 40° C (ASTM D445)	42.0	100	195
CCScSt @ 100° C (ASTM D445)	6.3	11.2	18.0
Viscosity Index (ASTM D2270)	97	97	96
Calcium, % wt.	.298	.298	.298
Zinc, % wt. (ASTM D4951)	.127	.127	.127
Phosphorus, % wt. (ASTM D4951)	.110	.110	.110
TBN (ASTM D2896)	7.9	7.9	7.9

The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice.

S•O•SSM Services for early problem detection

Protect your investment with Cat S•O•S oil analysis, the ultimate detection and diagnostic tool for your equipment. S•O•S helps you detect potential problems before they can lead to major failures and costly unscheduled downtime.

Cat Filters: Complete protection for your engine

Combine Cat Fluids with Cat Filters for the highest level of contamination control and protection for your machine. We recommend Cat Filters for all Cat machine applications.

Health and Safety

Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin or respiratory irritation. Always observe good hygiene measures. Read and understand the Material Safety Data Sheet (MSDS) before using this product. For a copy of the MSDS, visit us on the web at www.catmsds.com.

CAT DEALERS DEFINE WORLD-CLASS PRODUCT SUPPORT.

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts keeps your entire fleet up and running to maximize your equipment investment.

BUILT FOR IT.™

