

Slide Sledge®

Multi-Head Hammer Repair Tool



Makes repairs safely and efficiently

Put away the dangerous hammer and chisel. One operator can safely and easily maneuver the Slide Sledge Multi-Head Hammer Repair Tool into hard-to-reach places, simplifying repairs while reducing operator effort and injury.

Available at Cat® Dealers, Slide Sledge is powered by sliding the steel drive bar back and forth, allowing the operator to deliver a precise impact—when and where it's needed. This eliminates inaccurate sledgehammer swings and damage to machinery.

CATERPILLAR®

Slide Sledge Multi-Head Hammer Repair Tool



Increases profitability

- Eliminates need for special equipment or additional operators
- Reduces preventative and unscheduled maintenance hours

Simplifies field maintenance and repairs

- Removes and installs pins on virtually any equipment
- Cuts through stripped or rusted bolts in seconds
- Reaches between ripper teeth for easy removal and installation
- Drives seals into place, quickly and easily
- Adapts to separator forks for fast, easy changeouts

Promotes a safer work environment

- Minimizes operator effort and risk of injury
- Reduces muscle strain through finger-pressure control
- Eliminates flying debris associated with hammer and chisel use

Adapts to numerous applications

- Accommodates interchangeable, application-specific tips that allow one tool to do the job of many
- Adapts to quick-change tips engineered to get the job done faster and easier

Delivers powerful, precise impact

- Uses an additional five-pound handle weight for additional impact
- Constructed of induction-hardened steel for long life



Multi-Head Hammers

- 272-1208 **9 lb | 30" Heavy Equipment and 272-1237 2" Pin Driver**
Compact 30" length; great for fitting into tight areas.
- 272-1212 **13 lb | 46" Heavy Equipment and 272-1237 2" Pin Driver**
Ideal for most standard applications.
- 272-1215 **14 lb | 30" Heavy Equipment BMF and 272-1237 2" Pin Driver**
Larger-diameter BMF series with compact 30" length allows tool to fit into tight areas while delivering *Biggest Maximum Force*.
- 272-1218 **21 lb | 46" Heavy Equipment BMF and 272-1237 2" Pin Driver**
Longer length and greater weight deliver *Biggest Maximum Force* for your toughest applications.



1/2" Diameter Pin Driver
272-1228
Recommended for pins and bolts greater than 1/2" up to 7/8" in diameter.



7/8" Diameter Pin Driver
272-1230
Recommended for pins greater than 7/8" up to 1-1/4" in diameter.



1-1/4" Diameter Pin Driver
272-1233
Recommended for pins greater than 1-1/4" up to 2" in diameter.



2" Diameter Pin Driver
272-1237
Recommended for pins greater than 2" up to 2-1/2" in diameter.



2-1/2" Diameter Pin Driver
272-1239
Recommended for pins greater than 2-1/2" up to 3" in diameter.



3" Diameter Pin Driver
272-1240
Recommended for pins greater than 3" up to 4" in diameter.



Tie Rod/Ball Joint Separator 3-tip Set
272-1222
Slide Sledge separator adapter and 11/16", 15/16", 1-1/8" forks.



Tie Rod/Ball Joint Separator Adapter
272-1223
Attach all Slide Sledge separator forks and most common forks available today.



5 lb Handle Weight
272-1253
Increases the Slide Sledge striking force by 5 lb; works with any of the four tools by threading onto tool handle.



Slide Sledge Bag
273-3527 (38" long)
273-3528 (52" long)
273-3529 (Hard shell tool case w/ custom foam and wheels 53x14")



Tie Rod/Ball Joint Separator Forks
11/16" 272-1224
15/16" 272-1225



1-1/8" 272-1226
1-7/16" 272-1227



Ripper Tooth Pin Removers 3/8" Diameter
272-1246
Use on pins as small as 3/8" and up to 1/2" with minimum tooth spacing of 2-3/4".



1/2" Diameter
272-1245
Use on pins as small as 1/2" and up to 3/4" with minimum tooth spacing of 3-1/2".



3/4" Diameter
272-1243
Use on pins as small as 3/4" and up to 1" with minimum tooth spacing of 4-1/2".



Ripper Tooth Pin Inserters 3/8" Diameter
272-1247
Use on pins as small as 3/8" and up to 1/2" with minimum tooth spacing of 2-3/4".



1/2" Diameter
272-1244
Use on pins as small as 1/2" and up to 3/4" with minimum tooth spacing of 3-1/2".



3/4" Diameter
272-1242
Use on pins as small as 3/4" and up to 1" with minimum tooth spacing of 4-1/2".



Curved Chisel Tip
272-1241
1-3/8" tip ideal for chopping away hardened debris and shearing metal bolts, pins and rivets up to 3/8", Grade 8.



Scarifier Tooth Tip
272-1251
Removes scarifier teeth on most motor graders. The fork design allows the technician to split the trenching arm where the scarifier tooth is forced fit.



Utility Wedge Tip
272-1252
All-purpose impact tool designed to separate parts and straighten steel with maximum force.



Fits plates with a 1/4" center hole over 1-1/4" OD



Bushing/Bearing/Seal Plate Driver
272-1248
Use the extreme power of the Slide Sledge Multi-Head Hammer to drive heavy duty plates without the cocking motion of a hammer and handle. Fits plates with a 1/4" center hole over 1-1/4" OD. (plates not included) [Bolt for Bushing/Bearing/Seal Plate Driver is 312-0980]



Fits plates with common 9/16" center hole



Race/Bearing/Seal Adapter
272-1249
Install races, bearings and seals with this adapter driver tip. Add drive plates to the end of the adapter in various combinations Fits plates with a common 9/16" center hole, up to 3/4" high (plates not included) [Bolt for Race/Bearing/Seal Driver is 312-0977]



Fits drivers with common 3/4" center hole



Bushing Driver Adapter
272-1250
Proper installation of bushings will be accomplished easily and quickly with this adapter driver tip. Fits drivers with a common 3/4" center hole, up to 7/8" high (drivers not included). [Nut for Bushing Driver is 312-0978]



Tire Bead Breaker, Small
287-2075
Break that bead faster and easier than ever before with the Slide Sledge Multi-Head Hammer. Small bead breaker has a head width of 2" for most standard applications.

Tire Bead Breaker, Large
287-2077
The perfect bead breaker for those tough jobs. Large bead breakers have a head width of 2-7/8", ideal for tractor-trailers, backhoes, motor graders and other large equipment.

Slide Sledge Repair Parts



SLIDE SLEDGE PART NUMBER FOR LISTED TOOL					
Number	Description	SS HE 9LB/30"	SS HE 13LB/46"	SS HE 14LB/30"	SS HE 21LB/46"
		272-1208	272-1212	272-1215	272-1218
1	Drive Bar Threaded Cap	312-0981	312-0981	312-0981	312-0981
2	Driver Bar	312-0984	312-0985	312-0986	312-0988
3	Drive Bar Rubber Hand Stop	312-1012	312-1012	312-1014	312-1014
4	Driver Bar Retaining Ring	312-0990	312-0990	312-0991	312-0991
5	Square Hand Guard	312-0992	312-0992	312-0993	312-0993
6	Slide Lock Pin	312-0996	312-0996	312-0996	312-0996
7	Drive Bar Tube	312-0999	312-1001	312-1002	312-1003
8	Plunger Kit	312-7677	312-7677	312-7678	312-7678
9	Plunger	312-1009	312-1009	312-1010	312-1010
10	Tip Kit	312-1011	312-1011	312-1011	312-1011

CAT® DEALERS DEFINE WORLD-CLASS PRODUCT SUPPORT.

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts keeps your entire fleet up and running to maximize your equipment investment.



PEHJ0115-01
www.cat.com

© 2007 Caterpillar • All Rights Reserved • Printed in USA
CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow" and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

CATERPILLAR®
TODAY'S WORK. TOMORROW'S WORLD.™