

# Cat® R2900

## PRODUCT COMPARISON

# Cat® R2900G

<b>Cat® C15</b>
393 hp (293 kW)
409 hp (305 kW)
409 hp (305 kW)
37,920 lb (17,200 kg)
114,837 lb (52,089 kg)
152,756 lb (69,289 kg)
60,298 lb (27,346 kg)
Yes
29.5 R29
18.9 mph (30.4 km/h)
Yes
Yes
Yes
Yes
Single Bolt-on
Yes
Wet
Standard
Yes
Product Link Elite (PLE)
133.9 in (3,401 mm)
448.2 in (11,384 mm)
125.0 in (3,176 mm)
8.2 - 11.6 yd³ (6.3-8.9 m³)

Cat Engine Model
<b>EU Stage V Option</b>
U.S. EPT Tier 3 (Option)
VR Engine Option
Nominal Payload Capacity
Empty Weight
Loaded Weight
Breakout force – Tilt
<b>Resigned Engine End Frame</b>
Tire Size
<b>Top Speed</b>
<b>Optional New Door Latch Monitoring System</b>
<b>Info Display Screen (EU Stage V Emission Model)</b>
<b>New Remote Mounted Transmission Coolers</b>
<b>Increased Modularity &amp; Improved Serviceability</b>
Fuel Tank
<b>Bolt-on Brake Release System (Recovery Hook)</b>
<b>Fire System</b>
<b>LED Lights</b>
<b>Optional High Ambient Radiator (Std for HRC)</b>
<b>Machine Health Monitoring</b>
Turning Radius (Inside Clearance)
Machine Length (bucket in dig position)
Machine Width (including standard bucket)
Bucket Sizes

<b>Cat® C15</b>
<b>No</b>
409 hp (305 kW)
409 hp (305 kW)
37,920 lb (17,200 kg)
110,692 lb (50,209 kg)
148,611 lb (67,409 kg)
60,298 lb (27,346 kg)
N/A
29.5 R29
18.5 mph (29.8 km/h)
No
No
No
N/A
<b>Dual</b>
Yes
Foam & Powder
Optional
No
VIMS
133.2 in (3,383 mm)
445 in (11,302 mm)
125 in (3,176 mm)
8.2 - 11.6 yd³ (6.3-8.9 m³)



[cat.com/MINING](http://cat.com/MINING)